



## RedHawk 3™

A simple, compact and cost-effective alarm and monitoring device

### FEATURES:

Affordable

Available in External or internal DIN-mounted models

External model with or without red alarm light

Standard alarming includes alarm input, power fail, com fail

Receive notifications by text, email or phone

Historical trending of all data from unit

Supports simplex and duplex pump setups

120VAC power input, 120VAC alarm input

Two 4-20mA inputs, one alarm input, two status inputs

Internal battery keeps unit powered in the event of a brief power failure

Integrated surge suppression on 120VAC power input & 120VAC Alarm input

The RedHawk 3™ is an affordable all-in-one solution for monitoring your processes. The external version of the RedHawk 3™ looks and functions like a standard alarm light and can notify you the moment your system goes into alarm.

The RedHawk 3™ supports multiple power options to work around your solution. Options such as 8-32VDC or 120VAC power, alarm input of 120VAC, or dry closure.

Simply connect your existing alarm light to the alarm input so that you can receive and collect vital alarm information to solve potential problems in your service area.

The RedHawk 3™ includes THREE 4-20mA sensor inputs, ONE alarm input, and TWO status inputs.

The RedHawk 3™ is a cellular-based, device that will monitor your process, collect data, and report any problems to you through a phone call, text, or e-mail.

The internal version of the RedHawk 3™ can be easily snapped onto DIN rail, providing all of the same alarming features as the external version.

Let Hawk SCADA help you adapt one of our newest products to your needs!



### Technical Specifications:

Supports simplex and duplex pump setups

120VAC power input, 120VAC alarm input

THREE 4-20mA sensor inputs, ONE alarm input, and TWO status inputs

Internal battery keeps unit powered in the event of a brief power failure

Integrated surge suppression on 120VAC power input & 120VAC Alarm input

